NSN 5905-00-864-3192

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-864-3192

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.859 inches
Terminal Length:
0.156 inches
Body Diameter:
0.750 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Body Length:
Between 0.328 inches and 0.391 inches
Overall Diameter:
Between 0.875 inches and 0.938 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
Between 0.350 inches and 0.391 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
50.000 kilohms single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-864-3192

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
0.375 in. Long bushing
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0