NSN 5905-00-864-3192

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-864-3192

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 0.859 inches |
| Terminal Length: |
| 0.156 inches |
| Body Diameter: |
| 0.750 inches |
| Shaft Diameter: |
| Between 0.124 inches and 0.126 inches |
| Body Length: |
| Between 0.328 inches and 0.391 inches |
| Overall Diameter: |
| Between 0.875 inches and 0.938 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 3 oclock |
| Nonturn Device Radius: |
| Between 0.350 inches and 0.391 inches |
| Screw Thread Diameter: |
| 0.250 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Locking bushing |
| Electrical Resistance Per Section: |
| 50.000 kilohms single section |
| Resistance Tolerance Per Section In Percent: |
| -20.0/+20.0 single section |
| Standard Taper Curve Per Section: |

A single section

NSN 5905-00-864-3192

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Special Features: |
|-----------------------------|
| 0.375 in. Long bushing |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A002a0