Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-865-0025

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

1.078 inches

## Body Diameter:

0.531 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.375 inches

## Mounting Bushing Length:

## 0.250 inches

**Body Length:** 

0.469 inches

## **Overall Diameter:**

0.765 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

295.0

## Maximum Stop Torque:

64.00 inch-ounces

## Nonturn Device Location:

At 3 oclock

## Nonturn Device Radius:

0.245 inches

## Mechanical Backlash In Deg Angular Rotation:

3.0

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Front end

# NSN 5905-00-865-0025

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0