NSN 5905-00-865-4975



View Online at	https://aerobasegroup.com/nsn/5905-00-865-4975
Section Quant	ity:
1	
Body Style:	
Cylindrical bush	ning mounted
Reliability Indi	cator:
Not established	
Overall Length	:
Between 1.312	inches and 1.656 inches
Body Diameter	:
Between 1.032	inches and 1.156 inches
Shaft Diamete	:
Between 0.248	inches and 0.251 inches
Shaft Length:	
Between 0.469	inches and 0.531 inches
Mounting Bus	ning Length:
Between 0.360	inches and 0.432 inches
Body Length:	
Between 0.468	inches and 0.750 inches
Overall Diamet	er:
1.515 inches	
Shaft Style:	
Round, slotted	
Actuator Type	
Single shaft	
Maximum Star	ting Torque:
6.00 inch-ounce	es
Maximum Stop	Torque:
128.00 inch-our	nces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-865-4975

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.