NSN 5905-00-865-4980

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



80.	ction Quantity:
5e (cuon quantity.
	dy Style:
	indrical bushing mounted
	liability Indicator:
	t established
	erall Length:
	tween 1.312 inches and 1.562 inches
	dy Diameter:
	32 mils and 1.156 centimeters
	aft Diameter:
Bet	tween 0.248 inches and 0.251 inches
Sha	aft Length:
Bet	tween 0.844 inches and 0.906 inches
Мо	unting Bushing Length:
Bet	tween 0.485 inches and 0.515 inches
Во	dy Length:
Bet	tween 0.468 inches and 0.656 inches
Ov	erall Diameter:
1.5	15 inches
Sha	aft Style:
Ro	und, slotted
Act	tuator Type:
Sin	gle shaft
Ма	ximum Starting Torque:
6.0	0 inch-ounces
Ма	ximum Stop Torque:
128	3.00 inch-ounces
No	nturn Device Location:
At 9	9 oclock
No	nturn Device Radius:
Dot	tween 0.515 inches and 0.547 inches

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-865-4980

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



750.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0