## NSN 5905-00-865-5461

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-865-5461 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 2.250 inches **Overall Height:** Between 0.296 inches and 0.328 inches **Overall Width:** 0.280 inches **Mounting Hole Diameter:** Between 0.060 inches and 0.102 inches **Shaft Diameter:** 0.386 inches **Shaft Length:** Between 0.984 inches and 1.016 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** 0.296 inches **Body Height:** Between 0.296 inches and 0.328 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.984 inches and 1.016 inches **Mounting Facility Quantity:** 2 **Terminal Location:** 

Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 100.0 kilohms single section

## NSN 5905-00-865-5461

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: