NSN 5905-00-865-5469

Precision Wire Wound Variable Resistor - Page 1 of 2



Precision wire wound variable Resistor - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5905-00-865-5469	
Section Quantity:	
1	
Body Style:	
Cylindrical w/readout	
Reliability Indicator:	
Not established	
Pilot Diameter:	
Between 0.4020 inches and 0.4060 inches	
Overall Length:	
Between 1.454 inches and 1.610 inches	
Body Diameter:	
0.734 mils and 0.766 centimeters	
Mounting Bushing Length:	
Between 0.328 inches and 0.360 inches	
Body Length:	
Between 0.969 inches and 1.031 inches	
Overall Diameter:	
Between 0.734 inches and 0.766 inches	
Actuator Type:	
Integral knob with counter	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 3600.0 and 3610.0	
Maximum Starting Torque:	
5.00 inch-ounces	
Maximum Running Torque:	
5.00 inch-ounces	
Maximum Stop Torque:	
20.00 inch-ounces	
Nonturn Device Location:	
At 12 oclock	
Nonturn Device Radius:	
Between 0.275 inches and 0.285 inches	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	

Terminal Location:

Rear end

Mounting Method:

Standard bushing

NSN 5905-00-865-5469

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3620.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: