NSN 5905-00-865-5656

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-865-5656 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.9683 inches and 0.9688 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Overall Length:** 1.515 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** Between 0.0570 inches and 0.0670 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.124 inches **Shaft Length:** Between 0.360 inches and 0.390 inches **Body Length:** 1.140 inches **Overall Diameter:** 1.285 inches **Mounting Lip Diameter:** 1.0620 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:**

0.70 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

NSN 5905-00-865-5656

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
300.0 all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 2nd section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-670.0/+670.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
8 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-865-5656

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0