NSN 5905-00-865-6372

Fiig: A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-865-6372

Towns and the Conflictent Of Basistan and In Born Bas Bas Calaines
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/+260.0
Electrical Resistance:
3.900 kilohms Resistance Tolerance In Percent:
-5.000/+5.000 Ambient Tempurature In Dea Coloius At Full Pated Bower.
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0
Inclosure Method:
Encapsulated Tamping True 2
Terminal Type: Ferrule
Reliability Indicator:
Not established Tagging II on other
Terminal Length:
Between 0.438 inches and 0.562 inches
Body Diameter:
Between 0.531 inches and 0.594 inches
Body Length:
Between 1.875 inches and 2.000 inches
Power Dissipation Rating In Watts:
29.000 free air
Cubic Measure (non-core):
0.554 cubic inches
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No