NSN 5905-00-865-8943

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-865-8943

Section Quantity:		
1		
Body Style:		
Cylindrical servo mounted		
Reliability Indicator:		
Not established		
Pilot Diameter:		
Between 0.6247 inches and 0.6250 inches		
Pilot Length:		
0.0620 inches		
Undercut Diameter:		
0.775 inches		
Undercut Width:		
0.0680 inches		
Body Diameter:		
0.880 inches		
Shaft Diameter:		
0.125 inches		
Shaft Length:		
0.750 inches		
Body Length:		
2.440 inches		
Mounting Lip Diameter:		
0.8750 inches		
Mounting Lip Depth:		
0.0620 inches		
Shaft Style:		
Round, slotted		
Shaft Bearing Type:		
Ball		
Actuator Type:		
Single shaft		
Effective Electrical Rotation In Deg Angular Rotation:		
3600.0		
Maximum Starting Torque:		
0.60 inch-ounces		
Maximum Running Torque:		
0.40 inch-ounces		
Maximum Stop Torque:		
160.00 inch-ounces		
Shaft End Play:		

0.003 inches

NSN 5905-00-865-8943



Precision Wire Wound Variable Resistor - Page 2 of 3	Gro
Shaft Runout:	
0.0003 inches	

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.0005 inches

Mechanical Backlash In Deg Angular Rotation:

0.1

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

1800.0 single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Function Conformity Per Section:

Single section terminal base linearity

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

2500.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

4 turret

NSN 5905-00-865-8943

Precision Wire Wound Variable Resistor - Page 3 of 3



Sh	elf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0