NSN 5905-00-865-9028

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-865-9028 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.510 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.813 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.448 inches **Overall Diameter:** 1.563 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.40 inch-ounces **Maximum Running Torque:** 0.30 inch-ounces **Maximum Stop Torque:** 100.00 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.002 inches **Lateral Runout:**

Pilot Diameter Runout: 0.002 inches

0.005 inches

NSN 5905-00-865-9028

Shaft Radial Play:

0.003 inches

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter: 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 20.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 4.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -1.0/+1.0 ohms single section **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 10000.0 single section **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

3 solder stud

40.0 single section

Terminal Type And Quantity:

NSN 5905-00-865-9028

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0