NSN 5905-00-865-9306

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-865-9306

0.00
Section Quantity:
1 Parks Chales
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.921 inches
Body Diameter:
0.640 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.421 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
0.234 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

NSN 5905-00-865-9306

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0