NSN 5905-00-866-0999

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-866-0999 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length: 3.718** inches **Body Diameter:** 1.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 2.094 inches **Overall Diameter:** 2.313 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:**

Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0

NSN 5905-00-866-0999

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
504.0 single section and 3096.0 single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Power Dissipation Rating Per Section In Watts:
6.9 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
2 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0