NSN 5905-00-866-1767

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-866-1767

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.250 inches
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Overall Diameter:
1.156 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
292.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
192.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Mechanical Backlash In Deg Angular Rotation:
1.5
Fragility Factor:

Moderately rugged

NSN 5905-00-866-1767

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Cubic Measure:
1.312 cubic inches
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+3.0 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section
and -2.0/+2.0 85 degrees celsius single section and +0.0/+4.5 120 degrees celsius single section and +0.0/+6.5 150 degrees celsius single
section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0