Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-867-6462

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

### **Reliability Indicator:**

Not established

### Terminal Length:

0.500 inches

### Mounting Hole Diameter:

0.094 inches

### Shaft Diameter:

0.150 inches

Shaft Length:

0.050 inches

### Body Length:

1.250 inches

#### **Body Width:**

0.140 inches

# Body Height:

0.350 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

### Center To Center Distance Between Terminals:

0.700 inches

### Lateral Distance Between Mounting Hole Centers:

1.000 inches

### **Mounting Facility Quantity:**

2

# **Terminal Location:**

Lower adjacent side two rows

# Mounting Method:

Terminal and unthreaded hole

# Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

10.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

9000.0



Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0