

View Online at <https://aerobasegroup.com/nsn/5905-00-867-6480>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.0300 inches

**Pilot Length:**

0.0400 inches

**Undercut Diameter:**

1.030 inches

**Undercut Width:**

0.0600 inches

**Body Diameter:**

1.093 inches

**Shaft Diameter:**

Between 0.1245 inches and 0.1249 inches

**Shaft Length:**

0.750 inches

**Body Length:**

1.125 inches

**Mounting Lip Diameter:**

1.0930 inches

**Mounting Lip Depth:**

0.0600 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

360.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

2.00 inch-ounces

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Fixed Tap Quantity Per Section:**

4 single section

**Resistance Tolerance Per Section In Percent:**

-25.0/+25.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

7 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0