

View Online at <https://aerobasegroup.com/nsn/5905-00-868-6664>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.8750 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.812 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

2.000 inches

**Shaft Diameter:**

0.2497 inches

**Shaft Length:**

2.125 inches

**Body Length:**

1.304 inches

**Mounting Lip Diameter:**

2.0000 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

321.0

**Maximum Starting Torque:**

7.00 inch-ounces

**Maximum Running Torque:**

5.00 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

30.0 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

340.0

**Function Conformity Tolerance Per Section:**

-0.30/+0.30 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections equation

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Test Data Document:**

80249-730159 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

10 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0