

View Online at <https://aerobasegroup.com/nsn/5905-00-869-2009>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Length:

0.0620 inches

Overall Length:

1.884 inches

Undercut Diameter:

1.312 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.438 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.626 inches

Body Length:

1.040 inches

Mounting Lip Diameter:

1.4380 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

349.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section absolute linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0