

View Online at <https://aerobasegroup.com/nsn/5905-00-869-2010>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.3120 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.312 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.453 inches

Shaft Diameter:

0.249 inches

Shaft Length:

0.688 inches

Body Length:

1.580 inches

Mounting Lip Diameter:

1.4380 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

349.0

Maximum Starting Torque:

1.60 inch-ounces

Maximum Running Torque:

1.10 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Shaft End Play:

0.0025 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Flange

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections absolute linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0