Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-870-2044

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.188 inches

First Flat Length:

0.063 inches

Flat Height:

0.047 inches

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

Body Length:

0.563 inches

Overall Diameter:

1.156 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-870-2044

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 20.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0