## NSN 5905-00-874-0982

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-874-0982 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.790 inches **Body Diameter:** 1.350 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** 0.880 inches **Mounting Bushing Length:** 0.380 inches **Body Length:** 0.910 inches **Overall Diameter:** 1.350 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.547 inches and 0.578 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom **Mounting Method:** 

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

10.0 kilohms single section

## NSN 5905-00-874-0982

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
310.0	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-0.3/+0.3 single section	
Actuator Travel Control Feature:	
Stops	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A002a0