NSN 5905-00-875-4600

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-875-4600

Reliability Indicator:
Not established
First Flat Length:
0.625 inches
Flat Height:
0.153 inches
Body Diameter:
0.937 inches
Shaft Diameter:
Between 0.187 inches and 0.250 inches
Shaft Length:
Between 1.062 inches and 1.375 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.875 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Dual concentric
Switch Operating Position:
Start of rotation
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.0 percent, rated amperes c and better industrial clears
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 all sections

NSN 5905-00-875-4600

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A all sections
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0