Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-875-4600

Section Quantity: 2 **Reliability Indicator:** Not established First Flat Length: 0.625 inches Flat Height: 0.153 inches **Body Diameter:** 0.937 inches Shaft Diameter: Between 0.187 inches and 0.250 inches Shaft Length: Between 1.062 inches and 1.375 inches Mounting Bushing Length: 0.375 inches **Body Length:** 1.875 inches Shaft Style: Round, slotted Switch Type: Rotary Switch Voltage Rating In Volts: 125.0 Actuator Type: Dual concentric **Switch Operating Position:** Start of rotation **Screw Thread Diameter:** 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 250.0 percent, rated amperes c and better industrial clears **Power Dissipation Rating Per Section In Watts:** 0.5 free air all sections **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0