NSN 5905-00-876-9186

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-876-9186

| 0.0137 ohms Resistance Tolerance In Percent: -10.000/+10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Electrical Resistance: |
|--|--|
| Ambient Tempurature In Deg Celsius At Full Rated Power: 5.0. Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Or Standard: Ew form Shelf Life: Na Unit Of Measure: | 0.0137 ohms |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 50.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Weight: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Terminals each end Test Data Document: 81349-mill-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Sheef Life: Na Unit Of Measure: | Resistance Tolerance In Percent: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Width: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Terminals Document: 81349-mili-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | -10.000/+10.000 |
| Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 425.0 Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Width: 2.000 inches Body Height: 2.000 inches Power Dissipation Rating in Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ever form Shelf Life: N/a Unit Of Measure: | Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 425.0 Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Width: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 50.0 |
| Inclosure Method: Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil15109 specification (includes engineering type bulletins, brochures, etc., that reffect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| Uninclosed Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 425.0 |
| Terminal Type: Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Inclosure Method: |
| Threaded stud Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Uninclosed |
| Reliability Indicator: Not established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Terminal Type: |
| Note established Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Threaded stud |
| Body Length: 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Reliability Indicator: |
| 17.250 inches Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Not established |
| Body Width: 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Body Length: |
| 10.750 inches Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 17.250 inches |
| Body Height: 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Body Width: |
| 2.000 inches Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 10.750 inches |
| Power Dissipation Rating In Watts: 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Body Height: |
| 19.200 free air Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 2.000 inches |
| Style Designator: Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Power Dissipation Rating In Watts: |
| Terminals each end Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 19.200 free air |
| Test Data Document: 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Style Designator: |
| 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Terminals each end |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | Test Data Document: |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| Specification Or Standard: Ew form Shelf Life: N/a Unit Of Measure: | format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| Ew form Shelf Life: N/a Unit Of Measure: | environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: N/a Unit Of Measure: | Specification Or Standard: |
| N/a Unit Of Measure: | Ew form |
| Unit Of Measure: | Shelf Life: |
| | N/a |
| | Unit Of Measure: |
| Demilitarization: | |
| | Demilitarization: |
| No | No |
| Fiig: | Fiig: |
| A001a0 | A001a0 |