NSN 5905-00-877-5172



View Online	at https://aerobasegroup.com/nsn/5905-00-877-5172
Section Qua	antity:
1	
Body Style:	
Cylindrical b	ushing mounted
Reliability Ir	ndicator:
Not establish	ned
Overall Len	gth:
Between 1.3	12 inches and 1.562 inches
Body Diame	eter:
Between 1.0	32 inches and 1.156 inches
Shaft Diame	eter:
Between 0.2	48 inches and 0.251 inches
Shaft Lengt	h:
Between 0.8	44 inches and 0.906 inches
Mounting B	ushing Length:
Between 0.3	44 inches and 0.390 inches
Body Lengt	h:
Between 0.4	68 inches and 0.656 inches
Overall Diar	neter:
1.515 inches	
Shaft Style:	
Round, slott	ed
Actuator Ty	pe:
Single shaft	
Maximum S	tarting Torque:
6.00 inch-ou	nces
Maximum S	top Torque:
128.00 inch-	ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

NSN 5905-00-877-5172

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
750.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
C single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A002a0