## NSN 5905-00-877-5730

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-877-5730

Section Quantity:
2
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.6250 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.687 inches
Undercut Width:
0.0570 inches
Body Diameter:
0.880 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.625 inches
Body Length:
2.000 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 percent, rated amperes c and better industrial clears
Power Dissipation Rating Per Section In Watts:
0.1 free air all sections
Resistance Tolerance Per Section In Percent:
-2.0/+1.0 all sections
Standard Taper Curve Per Section:

A all sections

## NSN 5905-00-877-5730

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No **Fiig:** 

A002a0