NSN 5905-00-877-5757

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-877-5757

Section Quantity:
1
Body Style:
Cylindrical studs mounted
Reliability Indicator:
Not established
Body Diameter:
0.630 inches
Mounting Stud Length:
0.145 inches
Body Length:
0.406 inches
Mounting Hole/stud Circle Diameter:
0.428 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Screw Thread Diameter:
0.073 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
72.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded stud
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Ctons

Stops

NSN 5905-00-877-5757

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A002a0