## NSN 5905-00-877-5821

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-877-5821

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
75.000 kilohms
Resistance Tolerance In Percent:
-10.000/+10.000
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
12.000 inches
Heat Sink Width:
12.000 inches
Heat Sink Thickness:
0.059 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
molodare metrica.
Encased
Encased
Encased Terminal Type:
Encased  Terminal Type:  Tab, solder lug
Encased  Terminal Type:  Tab, solder lug  Terminal Length:
Encased  Terminal Type:  Tab, solder lug  Terminal Length:  0.406 inches
Encased  Terminal Type:  Tab, solder lug  Terminal Length:  0.406 inches  Body Length:
Encased  Terminal Type:  Tab, solder lug  Terminal Length:  0.406 inches  Body Length:  1.969 inches
Encased  Terminal Type: Tab, solder lug  Terminal Length: 0.406 inches  Body Length: 1.969 inches  Body Width:
Encased  Terminal Type:  Tab, solder lug  Terminal Length:  0.406 inches  Body Length:  1.969 inches  Body Width:  0.625 inches
Encased  Terminal Type: Tab, solder lug  Terminal Length: 0.406 inches  Body Length: 1.969 inches  Body Width: 0.625 inches  Body Height:
Encased  Terminal Type: Tab, solder lug  Terminal Length: 0.406 inches  Body Length: 1.969 inches  Body Width: 0.625 inches  Body Height: 0.625 inches
Encased  Terminal Type: Tab, solder lug  Terminal Length: 0.406 inches  Body Length: 1.969 inches  Body Width: 0.625 inches  Body Height: 0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches
Encased  Terminal Type:  Tab, solder lug  Terminal Length:  0.406 inches  Body Length:  1.969 inches  Body Width:  0.625 inches  Body Height:  0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Encased Terminal Type: Tab, solder lug Terminal Length: 0.406 inches Body Length: 1.969 inches Body Width: 0.625 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches Power Dissipation Rating In Watts:
Encased Terminal Type: Tab, solder lug Terminal Length: 0.406 inches Body Length: 1.969 inches Body Width: 0.625 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches Power Dissipation Rating In Watts: 15.000 free air
Encased Terminal Type: Tab, solder lug Terminal Length: 0.406 inches Body Length: 1.969 inches Body Width: 0.625 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches Power Dissipation Rating In Watts: 15.000 free air Mounting Hole Size: 0.125 inches
Encased Terminal Type: Tab, solder lug Terminal Length: 0.406 inches Body Length: 1.969 inches Body Width: 0.625 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches Power Dissipation Rating In Watts: 15.000 free air Mounting Hole Size:

N/a

## NSN 5905-00-877-5821

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0