NSN 5905-00-877-6170

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-877-6170 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.328 inches **Overall Height:** Between 0.297 inches and 0.328 inches **Overall Width:** Between 0.265 inches and 0.290 inches **Mounting Hole Diameter:** Between 0.086 inches and 0.093 inches **Shaft Diameter:** Between 0.120 inches and 0.130 inches **Shaft Length:** Between 0.031 inches and 0.062 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.265 inches and 0.290 inches **Body Height:** Between 0.297 inches and 0.328 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:**

30.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

7920.0

NSN 5905-00-877-6170

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab w/wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**