NSN 5905-00-877-9743

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-877-9743 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Terminal Length:** 6.000 inches **Overall Height:** Between 0.280 inches and 0.374 inches **Overall Width:** Between 0.235 inches and 0.300 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches **Shaft Diameter:** Between 0.100 inches and 0.140 inches **Shaft Length:** Between 0.036 inches and 0.077 inches **Body Length:** Between 1.218 inches and 1.282 inches **Body Width:** Between 0.235 inches and 0.300 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 100.000 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0

NSN 5905-00-877-9743

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
|--|
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -250.0/+250.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.7 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-milr22097-1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

Demilitarization:

No

Fiig:

A002a0