

View Online at <https://aerobasegroup.com/nsn/5905-00-877-9813>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.448 inches

**Body Diameter:**

0.850 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.850 inches

**Mounting Bushing Length:**

0.310 inches

**Body Length:**

1.448 inches

**Overall Diameter:**

0.850 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

0.40 inch-ounces

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

2.5 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-25.0/+25.0 single section

**Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Test Data Document:**

80378-215-01117-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0