Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-877-9814

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

0.125 inches

- Shaft Length:
- 0.050 inches

Body Length:

#### 1.250 inches

Body Width:

## 0.290 inches

**Body Height:** 

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

8640.0

### Lateral Distance Between Mounting Hole Centers:

1.000 inches

**Mounting Facility Quantity:** 

2

Terminal Location:

Rear end

### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

200.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

9720.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+0.0 single section

## Power Dissipation Rating Per Section In Watts:

1.0 free air single section



### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Actuator Travel Control Feature:

Clutch

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0