NSN 5905-00-878-1957

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-878-1957 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.560 inches **Overall Height:** 0.500 inches **Overall Width:** Between 0.182 inches and 0.197 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.092 inches **Shaft Length:** 0.093 inches **Body Length:** 0.500 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** Between 0.515 inches and 0.530 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end

Mounting Method: Terminal and unthreaded hole **Electrical Resistance Per Section:** 5.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

NSN 5905-00-878-1957

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**