NSN 5905-00-878-4366

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-878-4366

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -400.0/+400.0 |
| Electrical Resistance: |
| 3.000 ohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+350.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.359 inches |
| Body Diameter: |
| 0.906 inches |
| Body Length: |
| 4.000 inches |
| Power Dissipation Rating In Watts: |
| 55.000 free air |
| Terminal Width: |
| 0.328 inches |
| Style Designator: |
| Radial terminal each end |
| Test Data Document: |
| 81349-milr26-3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |