Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-878-8736

Section Quantity:

1

Body Style:

Rectangular w/bushing/slot mounted

Reliability Indicator:

Not established

Overall Length:

6.250 inches

Overall Height:

0.500 inches

Overall Width:

0.285 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.083 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.500 inches

Body Width:

0.285 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

Between 0.515 inches and 0.530 inches

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

32.0

2

N/a

No Fiig:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Facility Quantity: Terminal Location: Rear end **Mounting Method:** Standard bushing and unthreaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: Unit Of Measure: **Demilitarization:** A002a0