NSN 5905-00-879-4083

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-879-4083

Electrical Resistance: 5,100 ohms Resistance Tolerance in Percent: 5,000 45,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25,0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25,0/4350.0 Inclosure Method: Encepsulated Perminal Type: Write lead Retiability Indicator: Not established Body Diameter: 2,0469 inches Body Length: 2,000 inches Power Dissipation Rating In Watts: 4,000 ree air Style Designator: Axial terminal each end Fest Data Document: 13,1349-miliz6-d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Via Jint Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 5.50 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 5.50 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 5.50. Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 5.50.49.50.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 5.50.49.50.0 Rempurature Method: 6.00.00 Inclosure Method: 6.00 Inclosure	-400.0/+400.0
Resistance Tolerance in Percent: 5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0/435.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 3.489 inches 30dy Length: 2.000 inches Power Dissipation Rating in Watts: 14.000 free air 85tyle Designator: Axial terminal each end Test Data Document: 1349-mil/26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 25cheff Life: Via Juint Of Messure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Method: Tempurature	5.100 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Empurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+350.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Regiability Indicator: Vot established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Xxial terminal each end Feet Data Document: 93/494-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Juliot Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 550.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 555.0/+350.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Incapsulated Ferninal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.469 inches Power Dissipation Rating In Watts: 14.000 fee air Style Designator: Axial terminal each end Fest Data Document: 131349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Joint Of Measure: - Demilitarization: No	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+350.0 Tempurature Method: Tencapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 10.469 inches 2000 inches 2000 inches 2000 inches 2000 inches 2000 inches 2001 inches 2001 inches 2001 inches 2002 inches inches inchesion Rating In Wattis: 14.000 free air 15tyle Designator: 2014 axial terminal each end Test Data Document: 2015 34349-miltz6-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 2015 axial terminal each end Test Data Document: 2015 34349-miltz6-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: 1001 Incl Measure: 2015 - Commilitarization: 1006 - Commilitarization: 1007 - Commilitarization: 1008 - Commilitarization: 1009 - Commilitarization: 1000 - Commilitarization: 1001 - Commilitarization: 1001 - Commilitarization: 1002 - Commilitarization: 1003 - Commilitarization: 1003 - Commilitarization: 1004 - Commilitarization: 1007 - Commilitarization: 1008 - Commilitarization: 1008 - Commilitarization: 1009 - Commilitarization: 1019 - Commilitarization: 1019 - Commilitarization: 1020 - Co	Ambient Tempurature In Deg Celsius At Full Rated Power:
Pempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Perminal Type: Wive lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: xixial terminal each end Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; boxcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Julit Of Measure: Demilitarization: No Ferminal Official School (Company) The Company of Tempurature Coefficient In Deg Celsius: Style Designation: No Ferminal Type: Perminal Type:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 nclosure Method: ncapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 14.000 free air Skyle Designator: kxial terminal each end Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Diameter: 0.469 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milit26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: No Filig:	350.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.2000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-miliz6-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Ferst Data Document: 181349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	-55.0/+350.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Avial terminal each end Fest Data Document: B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Figi:	Inclosure Method:
Action in the lead Reliability Indicator: Not established Rody Diameter: 0.469 inches Rody Length: 0.000 inches Power Dissipation Rating In Watts: 14.000 free air Rely Length: 0.468 posignator: 0.468 posignator: 0.469 posignator: 0.469 posignator Rating In Watts: 14.000 free air Rely Length: 0.469 posignator Rating In Watts: 14.000 free air Rely Length: 0.469 posignator: 0.469 posignator Rating In Watts: 14.000 free air Rely Length: 0.469 posignator: 0.469 posignator Rating In Watts: 14.000 free air Rely Length: 0.460 posignator: 0.460 posignator 0.460 posignator 0.460 posi	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Terminal Type:
Note established Body Diameter: Diagony Diameter: Diagony Diameter: Diagony Length: Di	Wire lead
30dy Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Reliability Indicator:
3.0469 inches 3.040 Length: 2.000 inches 2.0	Not established
Body Length: 2,000 inches Power Dissipation Rating In Watts: 14,000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Junit Of Measure: Demilitarization: No Single:	0.469 inches
Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Length:
Axial terminal each end Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No	2.000 inches
Style Designator: Axial terminal each end Fest Data Document: 31349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	14.000 free air
Fest Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fig:	Style Designator:
B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No -	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
0004-0	Fiig:
AUUTAU	A001a0