Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-879-6949

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

0.250 inches

## Shaft Diameter:

0.125 inches

#### Shaft Length:

0.190 inches

## Mounting Bushing Length:

0.190 inches

## Body Length:

## 0.305 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

270.0

## Screw Thread Diameter:

0.138 inches

## Screw Thread Series Designator:

Unf

## Screw Thready Qty Per Inch (tpi):

40.0

## **Terminal Location:**

Rear end

## **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

10.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# NSN 5905-00-879-6949

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Stops

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0