

View Online at <https://aerobasegroup.com/nsn/5905-00-879-7222>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Shaft Diameter:**

Between 0.124 inches and 0.126 inches

**Shaft Length:**

0.587 inches

**Mounting Bushing Length:**

Between 0.734 inches and 0.766 inches

**Body Length:**

Between 0.469 inches and 0.500 inches

**Body Width:**

Between 0.484 inches and 0.516 inches

**Body Height:**

Between 0.484 inches and 0.516 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 290.0 and 300.0

**Maximum Starting Torque:**

4.50 inch-ounces

**Maximum Running Torque:**

4.50 inch-ounces

**Maximum Stop Torque:**

48.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 0.234 inches and 0.266 inches

**Fragility Factor:**

Moderately delicate

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.121 cubic inches

**Electrical Resistance Per Section:**

20.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

Between 290.0 and 300.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0