NSN 5905-00-879-7513

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-879-7513

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.500 inches
Body Diameter:
0.938 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.750 inches
Overall Diameter:
1.125 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:

Standard bushing

NSN 5905-00-879-7513

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:	
Switch	
Electrical Resistance Per Section:	
250.0 kilohms single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
30.0/+30.0 single section	
Switch Current Type And Rating In Amps:	
3.000 ac/dc	
Standard Taper Curve Per Section:	
A single section	
Ferminal Type And Quantity:	
5 tab, solder lug	
Shelf Life:	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A002a0	