

View Online at <https://aerobasegroup.com/nsn/5905-00-879-7716>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.0300 inches

Pilot Length:

0.0450 inches

Undercut Diameter:

1.030 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.109 inches

Angle Of Mounting Hole In Deg:

90.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.125 inches

Shaft Length:

0.640 inches

Body Length:

0.885 inches

Mounting Lip Diameter:

1.1090 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

0.625 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

1.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

230.0 all sections

Power Dissipation Rating Per Section In Watts:

20.0 free air all sections

Function Conformity Per Section:

All sections absolute conformity

Fixed Tap Quantity Per Section:

1 all sections

Tap Location Tolerance Per Section:

-50.0/+50.0 ohms all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

500.0 all sections

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0