## NSN 5905-00-879-7726

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-879-7726 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0300 inches Pilot Length: 0.0450 inches **Overall Length:** 0.910 inches **Undercut Diameter:** 1.03000 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.109 inches **Angle Of Mounting Hole In Deg:** 30.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 0.120 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.275 inches **Body Length:** 0.635 inches **Mounting Lip Diameter:** 1.1090 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 0.625 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:** 360.0

## NSN 5905-00-879-7726

Precision Nonwire Wound Variable Resistor - Page 2 of 3



| Screw Thread Diameter:  |
|---|
| 0.112 inches  |
| Screw Thread Series Designator:   |
| Unc   |
| Screw Thready Qty Per Inch (tpi):   |
| 40.0  |
| Mounting Facility Quantity:   |
| 3   |
| Terminal Location:  |
| Lower adjacent side single row  |
| Mounting Method:  |
| Threaded hole   |
| Electrical Resistance Per Section:  |
| 1.0 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:                                      |
| 360.0   |
| Function Conformity Tolerance Per Section:                                  |
| -0.50/+0.50 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 230.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 20.0 free air single section  |
| Function Conformity Per Section:  |
| Single section absolute linearity   |
| Fixed Tap Quantity Per Section:   |
| 1 single section  |
| Resistance Tolerance Per Section In Percent:                                |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Continuous motion   |
| Tap Location From Ccw Terminal Per Section In Ohms:                         |
| 500.0 single section  |
| Function Characteristic Per Section:  |
| Single section linear   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 single section   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5905-00-879-7726

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0