

View Online at <https://aerobasegroup.com/nsn/5905-00-879-7727>

**Section Quantity:**

1

**First Flat Length:**

Between 0.230 inches and 0.250 inches

**Flat Height:**

Between 0.105 inches and 0.110 inches

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.0

**Shaft Diameter:**

Between 0.1245 inches and 0.1250 inches

**Mounting Lip Diameter:**

0.89000 inches

**Shaft Bearing Type:**

Bearing

**Contact Arm Electrical Off Position:**

Fully cw

**Actuator Type:**

Double ended shaft

**Maximum Starting Torque:**

0.75 inch-ounces

**Electrical Resistance Per Section:**

1.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Function Conformity Per Section:**

Single section absolute linearity

**Fixed Tap Quantity Per Section:**

3 single section

**Tap Location Tolerance Per Section:**

-1.0/+1.0 ohms single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Criticality Code Justification:**

Abwv

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

74.0 single section

**Standard Taper Curve Per Section:**

A single section

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0