

View Online at <https://aerobasegroup.com/nsn/5905-00-879-7727>

Section Quantity:

1

First Flat Length:

Between 0.230 inches and 0.250 inches

Flat Height:

Between 0.105 inches and 0.110 inches

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

Between 0.1245 inches and 0.1250 inches

Mounting Lip Diameter:

0.89000 inches

Shaft Bearing Type:

Bearing

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Double ended shaft

Maximum Starting Torque:

0.75 inch-ounces

Electrical Resistance Per Section:

1.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Function Conformity Per Section:

Single section absolute linearity

Fixed Tap Quantity Per Section:

3 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 ohms single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Criticality Code Justification:

Abwv

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

74.0 single section

Standard Taper Curve Per Section:

A single section

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0