NSN 5905-00-879-9499

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-879-9499 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.141 inches **Body Diameter:** 1.094 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.266 inches **Overall Diameter:** 1.874 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 292.0 **Maximum Starting Torque:** 12.00 inch-ounces **Maximum Running Torque:** 12.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches Mechanical Backlash In Deg Angular Rotation:

3.0 Screw Thread Diameter:

0.375 inches

NSN 5905-00-879-9499

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef Control of the C
Screw Thready Qty Per Inch (tpi):
32.0
Ferminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.2 gallons per minute c and better industrial clears
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-0.0/+10.0 -55 degrees celsius 2nd section and +0.0/+5.0 -25 degrees celsius 2nd section and +0.0/+2.0 0 degrees celsius 2nd section and
3.5/+3.5 85 degrees celsius 2nd section and +0.0/+7.5 120 degrees celsius 2nd section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
20.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:
10.000/+10.000 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Ferminal Type And Quantity:
Stab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0