NSN 5905-00-880-0881

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-880-0881

Electrical Resistance: 10.000 ohms Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.378 inches Body Length: 0.778 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.336 inches Body Length: 2.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.000 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Fest Data Document:
31349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-22684/4 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0