

View Online at <https://aerobasegroup.com/nsn/5905-00-880-0909>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.313 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

Body Length:

0.688 inches

Overall Diameter:

1.063 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

80.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.250 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

3.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 290.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

12.5 heat sink single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0