## NSN 5905-00-880-2325

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-880-2325

Electrical Resistance:  1.600 ohms  Resistance Tolerance In Percent:  -5.000/+5.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.094 inches  Body Length:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-99737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9911-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9911-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9911-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shell Life: Na Unit Of Measure:	
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.094 inches Body Length: 0.094 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing, original equipment manufacturer drawing, sheefication, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing) and 13499-746-9811-96 drawing (this is the basic governing drawing) and 13499-746-9811-96 drawing (this is the basic gov	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9911-95 tharwing (this is the basic governing drawing, original equipment manufacturer drawing, shell Life: Na Unit Of Measure:	1.600 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Jength: 0.531 inches Power Dissipation Rating In Watts: 1.000 fee air Style Designator: 3499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-96 trawing. Shel Life: Na Unit Of Measure:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-95 drawing (this is the basic governing drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-95 drawing (this is the basic governing drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-95 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Fiig:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-95 drawing (this is the basic governing drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life:  Via Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:  N/a Unit Of Measure:  Demilitarization: No Filg:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing) original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.531 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	-55.0/+150.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.094 inches  Body Length: 0.531 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.094 inches  Body Length: 0.531 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-95 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 13499-746-9811-95 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Encapsulated
Reliability Indicator:  Not established  Body Diameter:  0.094 inches  Body Length: 0.531 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Terminal Type:
Not established  Body Diameter:  0.094 inches  Body Length:  0.531 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Wire lead
Body Diameter:  0.094 inches  Body Length:  0.531 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  1.3499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Reliability Indicator:
0.094 inches  Body Length: 0.531 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Length:  0.531 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
O.531 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-9999 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.094 inches
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Length:
1.000 free air  Style Designator: Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.531 inches
Style Designator:  Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-99 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	1.000 free air
Test Data Document:  13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-98 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-99 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-99 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	13499-746-9737-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-746-9811-99
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any
N/a Unit Of Measure: Demilitarization: No Fiig:	specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0