NSN 5905-00-880-2964

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-880-2964

Electrical Resistance: 24.300 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Avaid terminal each end Teste Data Document: 31249-mili2e-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Va Unit Of Measure: — Demilitarization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miliz26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Wig Unit Of Measure: — Demilitarization: No Filig:	-30.0/+30.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.004 inches Body Length: 1.000 free air Style Designator: Avial terminal each end Test Data Document: 131349-milize-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; secludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: — Demilitarization: No	Electrical Resistance:
Analysis of Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating in Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 91349-milize-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wia Unit Of Measure:	24.300 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reglability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.096 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Avaia terminal each end Test Data Document: Bai394-miltr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: Bat49-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Wa Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 45.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.0094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avaid terminal each end Tests Data Document: 81349-mitr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: No Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Encapsulated Reliability Indicator: Not established Body Diameter: -0.094 inches Body Length: -0.406 inches Power Dissipation Rating In Watts: -1.000 free air Style Designator:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Diameter: 0.095 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-miliz6-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0,049 inches Body Length: 0,406 inches Power Dissipation Rating In Watts: 1,000 free air Style Designator: Axial terminal each end Test Data Document: 131349-miliz6-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.). Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Avial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Terminal Type:
Note established Body Diameter: D.094 inches Body Length: D.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Wire lead
Body Length: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Not established
Body Length: 0.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
20.406 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.094 inches
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Style Designator: Axial terminal each end Test Data Document: B1349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.406 inches
Style Designator: Axial terminal each end Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: B1349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 free air
Test Data Document: 81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
B1349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
N001a0	Fiig:
	A001a0