NSN 5905-00-880-5453

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-880-5453

0.00.00.00
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.7495 inches and 0.7500 inches
Pilot Length:
Between 0.0570 inches and 0.0670 inches
Overall Length:
2.205 inches
Undercut Diameter:
0.781 inches
Undercut Width:
0.0570 inches
Body Diameter:
Between 0.870 inches and 0.880 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.594 inches and 0.656 inches
Body Length:
1.580 inches
Overall Diameter:
1.115 inches
Mounting Lip Diameter:
Between 0.8700 inches and 0.8800 inches
Mounting Lip Depth:
Between 0.0570 inches and 0.0670 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.40 inch-ounces
Maximum Stop Torque:

240.00 inch-ounces

NSN 5905-00-880-5453

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Servo mounting
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3785.0
Function Conformity Tolerance Per Section:
-0.02/+0.02 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 free air single section
Function Conformity Per Section:
Single section terminal base linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
88818-c603100243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No