

View Online at <https://aerobasegroup.com/nsn/5905-00-880-8419>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

2.030 inches

Terminal Length:

1.500 inches

Overall Height:

0.535 inches

Overall Width:

Between 0.182 inches and 0.197 inches

Mounting Hole Diameter:

Between 0.070 inches and 0.076 inches

Shaft Diameter:

Between 0.078 inches and 0.088 inches

Shaft Length:

Between 0.025 inches and 0.045 inches

Body Length:

Between 0.525 inches and 0.535 inches

Body Width:

Between 0.182 inches and 0.197 inches

Body Height:

Between 0.490 inches and 0.510 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.282 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.513 inches and 0.526 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.125 inches and 0.157 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0